

AUAV00088 Dulux Avista Slip Reducing Additive Crushed Glass Coarse

Introduction

Product Code
FD278015-5KG

Product Overview and Image

Dulux Avista Slip Reducing Crushed Glass is a clear glass additive that can be applied via hand broadcast to increase the slip resistance of Dulux Avista sealers & epoxies.



Features and Benefits

- Increases the slip resistance of concrete surfaces
- Compatible for use with all Dulux Avista sealers & epoxies
- Can be used on plain, stamped, stencilled or polished concrete

Uses

Dulux Avista Slip Reducing Crushed Glass is a coarse granulated product formulated to increase the slip resistance of most concrete surfaces, including stamped, stencilled, plain or polished concrete. It can also be used with any of the Dulux Avista sealers or epoxies.

Note: Dulux Avista Crushed Glass is not recommended for use on exposed aggregate concrete.

Typical Properties			
Components 1			
Shelf Life Indefinite in unopened container and stored in cool, dry conditions			
Sizes 5KG			
Application Methods Hand broadcast			
Specifications			
	Min	Max	Recommended
Theoretical Spread Rate (m ² /L)	<input type="text" value="100"/>	<input type="text" value="150"/>	<input type="text"/>
Typical Property Notes Chemical nature: Inorganic Solubility in water: Insoluble Solubility in Common Organic Solvents: Insoluble Sieve: approximate particle size 0.45 - 0.68 mm			

Slip Rating			
Surface Finish	Finish Coat	Slip Reducing Additive	Result
Steel Trowel finished concrete	Dulux Avista Tintable Sealer Semi-Gloss	Dulux Avista Slip Reducing Crushed Glass	P5
Steel Trowel finished concrete	Dulux Avista General Purpose Sealer Semi-Gloss	Dulux Avista Slip Reducing Crushed Glass	P5
Steel Trowel finished concrete	Dulux Avista General Purpose Sealer Matt	Dulux Avista Slip Reducing Crushed Glass	P4
Steel Trowel finished concrete	Dulux Avista Extended Wear Sealer	Dulux Avista Slip Reducing Crushed Glass	P4
Steel Trowel finished concrete	Dulux Avista Waterbased Sealer	Dulux Avista Slip Reducing Crushed Glass	P5
Steel Trowel finished concrete	Dulux Avista 2 Pack Urethane Sealer	Dulux Avista Slip Reducing Crushed Glass	P5

Maintenances
Check TDS of relevant Dulux Avista product for recommended maintenance.

Application Guide
Surface Preparation Check TDS of relevant Dulux Avista product for recommended surface preparation.
Application Procedure and Equipment Apply a coat of Dulux Avista sealer or epoxy over an area of about 2-5m ² . While surface is still wet, broadcast by hand sufficient Anti Slip in an upward motion to supply the slip resistance needed. It is important to apply crushed glass evenly, or the physical appearance can be altered slightly. When all of the designated surface is covered with crushed glass, allow the surface to dry. Apply a final coat of sealer or epoxy over the whole area to seal the crushed glass in place. Note: For systems with more than 2 coats of sealer or epoxy, the crushed glass should be applied between the final 2 coats.

Health and Safety

SDS Number
PAR009617

SDS Link
[View SDS Link](#)

Please refer to SDS Link. In case of emergency, please call 1800 220 770.

Precautions and Limitations

High levels of slip reducing crushed glass may detract from the appearance, and lower gloss levels.
High levels of slip reducing crushed glass can make cleaning more difficult.
Slip resistance achieved will vary depending on finish of the concrete, amount of crushed glass additive used & evenness of application.

Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from www.duspecplus.com.au. Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.