

## AUAV00119 Dulux Avista Solvent

### Introduction

Product Code  
**278182-4L**  
**1278182- 10L**  
**278182- 20L**

### Product Overview and Image

Dulux Avista® General Purpose Solvent can be used as a dilutant for Dulux Avista solvent based sealers as required, and to clean tools and equipment.



### Features and Benefits

- General purpose solvent
- Excellent solubility
- Colourless
- Non-foaming
- Use to clean tools and equipment
- Can be used as a dilutant for Dulux Avista solvent based sealers

### Uses

Dulux Avista Solvent is useful in cleaning tools, equipment and also to reactivate existing acrylic resins. It can also be used to dilute solvent based Dulux Avista sealers (see relevant sealer TDS for details).

### Typical Properties

Typical Property Notes  
Colour: Clear  
Chemical Nature: Aromatic Hydrocarbon Solvent  
Cas No: 1330-20-7  
Flash point (close cup): 24°Celsius T.C.C.  
Boiling point: 137.5°C  
Density @ 20degreesC: 0.87  
Slubility in water: Immiscible  
Explosive limits: Lower 1% - Upper 6%  
Storage: Store in a cool, dry area and keep container sealed.

**Application Guide**

Surface Preparation

**Solvent Wash**  
Apply Dulux Avista Solvent using a solvent resistant broom or roller, work in to surface until existing coating becomes tacky. Once dry enough to walk on, the resealing process can begin.

It can also be used to dilute solvent based Dulux Avista sealers (see relevant sealer TDS for details).

**Health and Safety**

SDS Number <b>PAR000576</b>	SDS Link <a href="#">View SDS Link</a>
Using Safety Precautions Appropriate PPE must be worn.	
<p><b>Please refer to SDS Link. In case of emergency, please call 1800 220 770.</b></p>	

**Precautions and Limitations**

Flammable  
 Harmful material when correct process is not followed.  
 Not suitable for water-based systems.

**Disclaimer**

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from [www.duspecplus.com.au](http://www.duspecplus.com.au). Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.